

1. LMW LX20TL3 (CNC)

DESCRIPTION	UNIT	LL20T L3
CAPACITY		
Swing Over bed	mm	510
Chuck dia. Max	mm	210
Max. Turning dia	mm	320
Max. Turning Length	mm	310*
Admit between Centres	mm	420
SPINDLE		
Spindle nose	type	A2-6
Hole through spindle	mm	61
Spindle speed	rpm	3000(3500)
Spindle motor power-15 min/Cont.(S6-40%/Cont.)	kW	11 / 7.5 (10.5 / 7)

2. LMW LR30TL7 (2018)

DESCRIPTION	UNIT	LL30T L7
CAPACITY		
Swing Over bed	mm	680
Chuck dia. Max	mm	304
Max. Turning dia	mm	470
Max. Turning Length	mm	700
SPINDLE		
Spindle nose	type	A2-8
Hole through spindle	mm	77
Spindle speed	rpm	3500
Spindle motor power	kW	18.5 / 15
FEED		
Cross travel X-axis	mm	260
Longitunal travel Z-axis	mm	760
Rapid traverse rate X/Z axes	m/min	20 / 24

3. LMW SMARTPLUS (2018)

DESCRIPTION	UNIT	SMARTURN PLUS
CAPACITY		
Swing Over bed	mm	480
Chuck dia. Max	mm	169
Max. Turning dia	mm	280
Max. Turning Length	mm	355
Admit between centres	mm	400
SPINDLE		
Spindle nose	type	Flat (Dia: 140)
Hole through spindle	mm	54
Spindle speed	rpm	4500
Spindle motor power(Cont./S6 40%)	kW	5.5 / 7.5v